Hydromechanical modeling of granular soils considering internal erosion

Jie Yang, Zhen-Yu Yin, Farid Laouafa, Pierre-Yves Hicher

► To cite this version:

Jie Yang, Zhen-Yu Yin, Farid Laouafa, Pierre-Yves Hicher. Hydromechanical modeling of granular soils considering internal erosion. Canadian Geotechnical Journal, 2020, 57 (2), pp.157-172. 10.1139/cgj-2018-0653 . ineris-03319074

HAL Id: ineris-03319074

<https://hal-ineris.archives-ouvertes.fr/ineris-03319074>

Submitted on 11 Aug 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Hydro-mechanical modeling of granular soils considering internal erosion

Author 1

Jie YANG, PhD candidate

INERIS, Verneuil en Halatte, France; Research Institute of Civil Engineering and Mechanics (GeM),
UMR CNRS 6183, Ecole Centrale de Nantes, France.

Email: doc.jie.yang@gmail.com

Author 2

Zhen-Yu YIN*, Associate Professor

Department of Civil and Environmental Engineering, The Hong Kong Polytechnic University, Hung
Hom, Kowloon, Hong Kong, China.

Email: zhenyu.yin@polyu.edu.hk, zhenyu.yin@gmail.com

Author 3

Farid LAOUAFA, PhD

INERIS, Verneuil en Halatte, France.

Email: farid.laouafa@ineris.fr

Author 4

Pierre-Yves HICHER, Emeritus Professor

Research Institute of Civil Engineering and Mechanics (GeM), UMR CNRS 6183, Ecole Centrale de
Nantes, France.

Email: pierre-yves.hicher@ec-nantes.fr

*Corresponding author:

Zhen-Yu YIN, Tel: +852 3400 8470; Fax: +852 2334 6389; Email: zhenyu.yin@polyu.edu.hk,
zhenyu.yin@gmail.com

27 **Abstract:**

28 This paper attempts to formulate a coupled practical model in the framework of continuum
29 mechanics to evaluate the phenomenon of internal erosion and its consequences on the mechanical
30 behavior of soils. For this purpose, a four-constituent numerical approach has been developed to
31 describe the internal erosion process. The detachment and transport of the fine particles have been
32 described by a mass exchange formulation between the solid and fluid phases. The stress-strain
33 relationship of the soil is represented by a non-linear incremental model. Based on experimental data,
34 this constitutive model has been enhanced by the introduction of a fines content dependent critical
35 state, which allows accounting for the influence of fines on soil deformation and strength. The
36 applicability of the practical approach to capture the main features of the internal erosion process and
37 its impact on the mechanical behavior of the eroded soil has been validated by comparing numerical
38 and experimental results of internal erosion tests on HK-CDG mixtures, which demonstrated that the
39 practical model was able to reproduce, with a reasonable success, the experimental data.
40 Furthermore, the influence of the stress state, the initial soil density, and the initial fraction of fines
41 have been analyzed through numerical simulations using the proposed model.

42 **Keywords:** Granular soils; internal erosion; hydro-mechanical coupling; critical state; fines content

44 **1. Introduction**

45 Internal erosion occurs when fine particles are plucked off by hydraulic forces and transported
 46 through the coarse matrix. The known causes are either a concentration of leak erosion, backward
 47 erosion, soil contact erosion, or suffusion (Bonelli and Marot 2008; Fell et al. 2003; Wan and Fell
 48 2004). This paper focuses on suffusion, which corresponds to the detachment and migration of fine
 49 particles within the voids of coarse particles by seepage flow. Subsequently, the induced
 50 modification of the soil microstructure may lead to deformations at the macroscopic scale and,
 51 therefore, influence significantly the mechanical behavior of the soil. Many damages and failures of
 52 embankment dams can be associated with internal erosion (Fell et al. 2003; Xu and Zhang 2009;
 53 Zhang and Chen 2006; Zhang et al. 2009; Rönnqvist et al. 2014). Foster et al. (2000) showed that
 54 nearly 46% of the damages of 128 embankment dams could be attributed to internal erosion.
 55 Besides, sinkholes and cavities triggered by internal erosion are frequently observed within dams and
 56 dikes (Muir Wood 2007; Sterpi 2003). Finally, internal erosion can also trigger slope failures and
 57 generate significant landslides (Crosta and Prisco 1999; Hu et al. 2018).

58 To evaluate the internal instability of filters in embankment dam, engineers have traditionally
 59 employed empirical methods (Burenkova 1993; Foster and Fell 2001; Kenney and Lau 1985, 1986;
 60 Kézdi 1979; Li and Fannin 2008; Sherard 1979; Wan and Fell 2008). Rönnqvist et al. (2014)
 61 compiled a database of 80 dams of which 23 dams suffered from documented internal erosion. Their
 62 gradation analysis demonstrated that empirical methods are capable of distinguishing dams with a
 63 probable occurrence of erosion from dams with no up-to-date indication of internal erosion.
 64 Laboratory tests further investigated the mechanics of internal erosion and the susceptibility of soil to
 65 seepage induced internal instability by using primarily the conventional rigid-walled permeameter
 66 under self-weight conditions (e.g. Kenney and Lau 1985, Skempton and Brogan 1994, Sterpi 2003,
 67 Wan and Fell 2008, Sibille et al. 2015a; Rochim et al. 2017). The eroded mass, the hydraulic

68 gradient and the flow rate were monitored to determine the susceptibility of seepage induced
69 instability by incorporating the post-erosion analysis of the particle size distribution. The initial fines
70 content and the history of the hydraulic loading appeared to play an important role in the
71 development of internal erosion (Sibille et al. 2015a; Rochim et al. 2017). It is important to add that
72 the soils constituting embankment dams or levees are usually subjected to complex stress states
73 (Zhang and Du 1997). To address this phenomenon, Moffat and Fannin (2006, 2011) developed a
74 rigid-wall permeameter with an axial loading system so that the onset of internal instability of
75 cohesionless soils under K_0 stress state could be investigated. More recently, advanced flexible wall
76 permeameters capable of controlling the stress on the tested specimen have been developed so that
77 the development of internal erosion under different stress states and the mechanical behavior of soils
78 during and after erosion could be investigated (e.g., Bendahmane et al. 2008; Chang and Zhang
79 2011; Marot et al. 2016; Ke and Takahashi 2014a; Slangen and Fannin 2016). Most of the studies
80 were conducted under an isotropic stress state. The results showed that the larger effective confining
81 pressure led to a less extent of internal erosion (Bendahmane et al. 2008; Mehdizadeh et al. 2017),
82 even if the deformation of the specimen caused by erosion was limited. Chang and Zhang (2011)
83 showed that, by performing internal erosion tests under different anisotropic stress states, the
84 maximum erosion rate, the variations in soil permeability, and the erosion induced deformation of
85 the specimen will all increase with the increase of the deviatoric stress. For the purpose of
86 investigating the influence of the loss of fine particles on the mechanical behavior of eroded soils,
87 they performed triaxial tests on eroded specimen under different stress paths. Drained triaxial tests
88 on eroded specimens indicated that the initially dilative stress-strain behavior changed to a
89 contractive behavior and the soil strength decreased under drained shearing (Chang and Zhang 2011;
90 Ke and Takahashi 2014a, 2014b, 2015). The undrained behavior of the original specimen changed
91 from a strain hardening behavior to a flow-type behavior with limited deformation after internal
92 erosion (Ke et al. 2016; Mehdizadeh et al. 2017).

93 Parallel to experimental studies, numerical approaches have also been proposed to describe the
94 erosion process, either within the framework of continuum mechanics by using finite element or
95 finite difference methods (Cividini and Gioda 2004; Papamichos et al. 2001; Stavropoulou et al.
96 1998; Vardoulakis et al. 1996; Zhang et al. 2013), or within a discrete framework by associating the
97 discrete element method to describe the dynamics of the granular solid phase to the computational
98 fluid dynamics to solve the interstitial fluid flow (Lominé et al. 2013; Mansouri et al. 2017; Reboul
99 2008; Sari et al. 2011; Sibille et al. 2015b; Zhang et al. 2018; Zhao and Shan 2013), mainly focused
100 on the hydraulic process, i.e. the evolution of the eroded mass and permeability. The mechanical part
101 was simplified by using an elastic model with induced damage parameters. Some attempts have also
102 been made to model the mechanical response to internal erosion by removing particles in granular
103 materials. Muir Wood et al. (2010) modeled the mechanical consequences of internal erosion by a
104 two-dimensional discrete element analysis and found that internal erosion changes the density state
105 of the material from dense to loose as they compared the current soil state to the critical state line.
106 Scholtès et al. (2010) developed a three-dimensional discrete element model and an analytical
107 micromechanical model to describe the mechanical responses induced by particle removal in
108 granular materials. They found that the mechanical behavior of the soil changes from dilative to
109 contractive with the removal of soil particles. However, this removal was based on the size of the
110 particles and their degree of interlocking, and the fluid phase was not considered. Hosn et al. (2018)
111 studied the macroscopic response during internal erosion and the post-internal erosion properties of
112 granular materials by particle removal, considering a one-way coupling between the fluid and the
113 solid phases via the discrete element and the pore scale finite volume methods. The erosion process
114 was simplified into the definition of the detached and transportable particles by calculating the
115 unbalance fluid force and by defining a controlling constriction size. Hicher (2013) presented a
116 numerical method to predict the mechanical behavior of granular materials subjected to particle
117 removal and concluded that the removal of soil particles may cause diffuse failure in eroded soil

118 masses. However, the process of real erosion was not considered. Therefore, it is of interest to
 119 develop a numerical method that will provide the modeling of the hydro-mechanical response of
 120 soils subjected to internal erosion.

121 Despite the relevance of the discrete element method to shed light onto the constitutive properties of
 122 granular materials, its computational cost remains a restrictive aspect which could become an
 123 obstacle wherever real soil structures such as embankment dams are concerned. Hence, it is
 124 necessary to develop the approaches that can take better into account the engineering boundary value
 125 problems. The objective of this paper is to formulate a numerical model within the framework of
 126 continuum mechanics to investigate the coupled hydro-mechanical behavior of soils subjected to
 127 internal erosion. First, an enhanced four-constituent model has been developed to describe the
 128 detachment and transport of fine particles induced by the fluid flow with more realistic consideration
 129 of the effects of the fines content and the shear stress level. This process has been coupled with an
 130 advanced critical state-based mechanical model, which has been enhanced to consider the effects of
 131 the evolution of the fines content. By assuming a homogenous sample, a practical simulation tool for
 132 triaxial erosion tests under mechanical loadings has also been proposed. Then, the predictive ability
 133 of the approach has been examined by simulating internal erosion tests on HK-CDG mixtures under
 134 mechanical loadings. Finally, the influence of the stress state, the initial density, and the initial fines
 135 content of the soil have been investigated by the developed numerical model.

136 **2. Coupled hydro-mechanical model**

137 According to Schaufler et al. (2013), it is possible to consider the saturated porous medium as a
 138 material system composed of 4 constituents in 2 phases: the stable fabric of the solid skeleton, the
 139 erodible fines, the fluidized particles and the pure fluid. The fines can behave either as a fluid-like
 140 (described as fluidized particles) or as a solid-like (described as erodible fines) material.

141 It is assumed that the seepage velocities $\mathbf{w}$ is given as the relative motion of the fluid phase $\mathbf{v}_l$ with
 142 respect to the solid phase $\mathbf{v}_s$. The relative motion of the pore fluid and the fluidized particles is
 143 neglected. The total discharge of the liquid $\mathbf{q}_w$ is then given as:

$$144 \quad \mathbf{q}_w(x, t) = \phi(x, t) \mathbf{w}(x, t) \quad \text{with} \quad \mathbf{w}(x, t) = \mathbf{v}_l - \mathbf{v}_s \quad (1)$$

145 where $\phi(x, t)$ is the porosity. Furthermore, in the framework of small transformations (small strains
 146 and small displacements), the strain of the solid skeleton is given by the symmetric part of the
 147 displacement gradient.

148 **2.1. Mass balances and transported particles**

149 The balance equations are derived based on the porous medium theory (de Boer 2000; Steeb and
 150 Diebels 2003; Uzuoka and Borja 2012). The local form of the volume balance of a constituent is
 151 deduced from the partial balance of mass (Vardoulakis et al. 1996), given as:

$$152 \quad \frac{\partial(n_i)}{\partial t} + \text{div}(n_i \mathbf{v}_i) = \hat{n} \quad (2)$$

153 where n_i and $\mathbf{v}_i$ denote, respectively, the volume fraction and the velocity of the corresponding
 154 constituent. The liquid-solid phase transition process has been accounted for by introducing a
 155 volumetric mass exchange term $\hat{n}$ in the corresponding mass balances for the 4 constituents. More
 156 details can be found in the Appendix A1.

157 A system of non-linear partial differential equations is deduced from the mass balance of the mixture
 158 system:

$$159 \quad \text{div}(\mathbf{q}_w) + \text{div}(\mathbf{v}_s) = 0 \quad (3)$$

$$-\frac{\partial \phi}{\partial t} + \operatorname{div}(\mathbf{v}_s) - \operatorname{div}(\phi \mathbf{v}_s) = \hat{n} \quad (4)$$

$$\frac{\partial(f_c)}{\partial t} - \frac{\partial(f_c \phi)}{\partial t} + \operatorname{div}(f_c \mathbf{v}_s) - \operatorname{div}(f_c \phi \mathbf{v}_s) = \hat{n} \quad (5)$$

$$\frac{\partial(c\phi)}{\partial t} + \operatorname{div}(c\mathbf{q}_w) + \frac{\partial(c\phi \mathbf{v}_s)}{\partial t} = -\hat{n} \quad (6)$$

where $\phi(x, t)$, $f_c(x, t)$ and $c(x, t)$ are the porosity, the amount of erodible fines and the concentration of the fluidized particles, respectively; $\hat{n}$ is the source term describing the exchange between the erodible fines and the fluidized particles; $\mathbf{v}_s$ is the velocity of the soil skeleton; $\mathbf{q}_w(x, t)$ is the total discharge of the pore fluid.

2.2. Balance of linear momentum

The model has been developed for geotechnical applications and it is not the aim of the present paper to present the thermodynamical setting of the erosion model. Therefore, the linear momentum balance equation of a constituent is given as follows under isothermal and quasi-static conditions:

$$\operatorname{div}(\boldsymbol{\sigma}_i) + \hat{\mathbf{p}}_i = 0, \quad \sum_i \hat{\mathbf{p}}_i = 0 \quad (7)$$

where $\boldsymbol{\sigma}_i$ is the total Cauchy stress tensor of the solid or liquid phase; $\hat{\mathbf{p}}_i$ is the interaction force between solid and liquid phases. In this configuration, further density driven momentum production (see Steeb and Diebels 2003) and body forces are not taken into account. Nevertheless, we assume that the process is slow, i.e. the inertia forces can be neglected. This equilibrium equation allows prescribing the total force $\mathbf{t} = \boldsymbol{\sigma} \cdot \mathbf{n}$ and the solid displacement $\mathbf{u}_s$ at the boundary of the body.

177 The partial Cauchy stresses σ_i for the two phases are derived as follows for a fluid saturated medium
 178 (Borja 2006):

$$179 \quad \sigma_s = \sigma' - (1 - \phi) p_w \mathbf{I}, \quad \sigma_l = -\phi p_w \mathbf{I} \quad (8)$$

180 where σ' is the effective stress tensor, calculated by the non-linear incremental constitutive model
 181 presented in the next section; p_w is the pore fluid pressure. Thus the set of equations (3)-(6) can be
 182 closed by:

$$183 \quad \text{div}(\sigma' - p_w \mathbf{I}) = 0 \quad (9)$$

184 2.3. Porous fluid flow

185 In this study, it is assumed that the flow in the porous medium is governed by Darcy's law which
 186 states that the flow rate is driven by the gradient of the pore fluid pressure $p_w(x, t)$:

$$187 \quad \mathbf{q}_w = -\frac{k(f_c, \phi)}{\eta_k \bar{\rho}(c)} \mathbf{grad}(p_w) \quad (10)$$

188 where $k(f_c, \phi)$ denotes the intrinsic permeability of the medium; η_k is the kinematic viscosity of the
 189 fluid; p_w is the pore fluid pressure; and $\bar{\rho}(c)$ is the density of the mixture defined as:

$$190 \quad \bar{\rho} = c \rho_s + (1 - c) \rho_f \quad (11)$$

191 with ρ_s the density of the solid and ρ_f the density of the fluid. For a material made of a mixture of
 192 coarse and fine grains, the intrinsic permeability $k(x, t)$ of the porous medium depends on the
 193 current porosity $\phi(x, t)$ and the fines content $f_c(x, t)$ as (Revil and Cathles 1999):

$$k = k_0 [1 - f_c (1 - \phi)]^{3m_k} \quad (12)$$

where m_k is a power index which varies with the pore geometry (Revil and Cathles 1999).

2.4. Mass exchange term

The variable $\hat{n}$ in Eqs. (4)-(6) is the volumetric mass exchange at any point in time, given by the following relation (Uzuoka et al. 2012):

$$\hat{n} = -\lambda_e (1 - \phi) (f_c - f_{c\infty}) |\mathbf{q}_w| \quad (13)$$

where $f_{c\infty}$ is the ultimate fines content after a long seepage period; λ_e is a material parameter. The erosion rate depends not only on the total discharge of fluid $\mathbf{q}_w$, but also on the residual fines content $(f_c - f_{c\infty})$. $f_{c\infty}$ is assumed to decrease when the hydraulic gradient increases as follows (Cividini et al. 2009):

$$f_{c\infty} = f_{c0} \left[\left(1 - \frac{\alpha_1}{\exp(\eta/M_p)} \right) \exp(-|\mathbf{q}_w|^{\alpha_3} \times 10^{\alpha_2}) + \frac{\alpha_1}{\exp(\eta/M_p)} \right] \quad (14)$$

where f_{c0} is the initial fines content, α_1 , α_2 and α_3 are material parameters. A mechanical component “ η ” defined later on is introduced into the definition of $f_{c\infty}$, in order to take into account the influence of the stress state on the erosion rate.

Note that the mass exchange term $\hat{n}$ is defined as a function of the porosity, the initial fines content, the flow rate and the stress state. There isn't any explicit expression to define the critical hydraulic gradient required to initiate the erosion or the soil skeleton deformation. All the unknown variables are coupled implicitly and solved by the system of the partial differential equations.

212 2.5. Critical state based soil model considering fines content effect

213 A non-linear incremental constitutive model including the critical state concept has been adopted
 214 (Yin et al. 2018a). The non-linear frictional behavior of the granular materials can be described by an
 215 asymptotic relation between the stress ratio η and the shear strain ε_d as follows:

$$216 \quad \eta = M_p \left(1 - e^{-\frac{G_\eta}{M_p} \varepsilon_d} \right) \quad (15)$$

217 where M_p is the maximum strength ratio; $G_\eta = 3G/p'$ is the initial stiffness; p' is the effective
 218 pressure; G is the shear modulus. The model has been enhanced by introducing a non-linear
 219 elasticity, a non-linear stress dilatancy, and the critical state concept (Jin et al. 2017; Jin et al. 2016;
 220 Jin and Yin 2018). More details of the model can be found in Yin et al. (2018a).

221 The constitutive equations under axisymmetric triaxial condition are briefly summarized as follows:

$$222 \quad \delta p' = K \left\{ \delta \varepsilon_v - A_d \left(M_{pt} - \frac{q}{p'} \right) \delta \varepsilon_d [1 - \exp(-d\eta)] \right\} \quad (16)$$

$$223 \quad \delta q = 3G \delta \varepsilon_d \left(1 - \frac{q}{p' M_p} \right) + \frac{q}{p'} \delta p' \quad (17)$$

224 with

$$225 \quad G = G_0 \frac{(2.97 - e)^2}{(1 + e)} \left(\frac{p'}{p_{at}} \right)^n, \quad K = K_0 \frac{(2.97 - e)^2}{(1 + e)} \left(\frac{p'}{p_{at}} \right)^n \quad (18)$$

$$226 \quad M_p = \frac{6 \sin \phi_p}{3 - \sin \phi_p}, \quad M_{pt} = \frac{6 \sin \phi_{pt}}{3 - \sin \phi_{pt}} \quad (19)$$

227 where ϕ_p and ϕ_{pt} are determined by

$$228 \quad \tan \phi_p = \left(\frac{e_c}{e} \right)^{n_p} \tan \phi_c, \quad \tan \phi_{pt} = \left(\frac{e_c}{e} \right)^{-n_d} \tan \phi_c \quad (20)$$

229 with the critical state void ratio e_c given by

$$230 \quad e_c = e_{cr0} - \lambda \left(\frac{p'}{p_{at}} \right)^\xi \quad (21)$$

231 where the stress ratio $\eta = q/p'$ under axisymmetric triaxial condition is defined by the deviatoric
 232 stress q ($q = \sigma_a - \sigma_r$) and the mean effective stress p' ($p' = (\sigma'_a + 2\sigma'_r)/3$), with σ_a and σ_r the
 233 axial and radial stress, respectively; the deviatoric strain increment $\delta\epsilon_d = 2(\delta\epsilon_a - \delta\epsilon_r)/3$ is a
 234 function of the axial and radial strain increments; $\delta\epsilon_v = \delta\epsilon_a + 2\delta\epsilon_r$ is the volumetric strain
 235 increment; K and G are the bulk and shear moduli with the reference bulk and shear moduli K_0 and
 236 G_0 ; Poisson's ratio $\nu = (3K_0 - 2G_0)/(6K_0 + 2G_0)$; the non-linear elastic constant n (typically 0.5-
 237 0.7); $p_{at} = 101.325 \text{ kPa}$ is the atmospheric pressure chosen as the reference stress; A_d and d are the
 238 stress-dilatancy parameters; e_{cr0} is the reference critical void ratio at extremely low confining
 239 pressure; λ and ξ are material constants controlling the non-linearity of the critical state line; ϕ_c is
 240 the critical friction angle.

241 Since the fines content evolves during internal erosion, the constitutive model needs to consider such
 242 internal soil mass evolution. According to Yin et al. (2014; 2016), e_{cr0} is a function of the evolutive
 243 fines content f_c , in order to unify the mechanical behavior of a sand-silt mixture for different fines
 244 contents:

$$e_{cr0} = [e_{hc,cr0}(1 - f_c) + af_c] \frac{1 - \tanh[\zeta(f_c - f_{th})]}{2} + e_{hf,cr0} \left(f_c + \frac{1 - f_c}{(R_d)^m} \right) \frac{1 + \tanh[\zeta(f_c - f_{th})]}{2} \quad (22)$$

where $e_{hc,cr0}$ and $e_{hf,cr0}$ are the reference critical void ratios for the pure sand and the pure silt, respectively. a , ζ , R_d , m and f_{th} are material constants: a controls the slope of the curve $e_{cr0} - f_c$ for the silty sand varying from -1.0 to 1.0. m controls the slope of the curve $e_{cr0} - f_c$ for the sandy silt varying from 0.0 to 1.0, f_{th} and ζ control the transition zone between the silty sand and the sandy silt. ζ controls the evolution rate of the transition zone ($\zeta = 20$ after Yin et al. 2014; 2016), f_{th} is the threshold fines content from a coarse grain skeleton to a fine grain skeleton, varying usually from 0.2 to 0.35 on the basis of existing experimental data; R_d is the ratio of the mean size of the coarse grains D_{50} to the mean size of the fine grains d_{50} . The material constants a , m and f_{th} can be determined by measuring the evolution of the minimum void ratio e_{min} versus f_c , which is obtainable at low experimental cost, as suggested by Yin et al. (2014; 2016). It should be pointed out that Eq. (22) is mathematically structured based on the hyperbolic tangent function to ensure a continuous and smooth transition domain; more validation and discussion can be found in Yin et al. (2014; 2016).

2.6. Hydro-mechanical responses of soils during internal erosion

Two main influences can be noted concerning the mechanical impact of the decrease of the fines content induced by internal erosion. First, according to Eq.(18), the increase of the void ratio can reduce the elastic moduli G and K , leading to increasing deformation of the granular assembly. The second consequence is linked to the interlocking features. The sliding resistance between particles has two origins: one is the friction between two particles, the other is related to the geometrical (topological) effect of the neighboring particles which will resist the sliding displacement of two

particles in contact, i.e. the interlocking effect. From a macroscopic standpoint, the first aspect is characterized by the internal friction angle ϕ_c , corresponding to the critical state; the second aspect is related to the density state, which will in turn influence the peak strength and the dilative/contractive behavior of the soil. In the model, this interlocking influence is taken into account by Eqs. (20)-(22), which relate the sliding resistance, controlled by the mobilized peak friction angle ϕ_p to the density state (e_c/e) of the assembly. Therefore, the loss of fine particles affects the interlocking, i.e. the density state, by changing simultaneously the void ratio e and the critical void ratio e_c . When a part of the fine particles is detached from the soil skeleton, the void ratio e increases, the critical void ratio e_c evolves according to the fines content f_c evaluated by Eqs. (21)-(22). According to Yin et al. (2014, 2016), in the case of a fine grain skeleton, the loss of fine particles will decrease the critical void ratio e_c . From a microscopic standpoint, the loss of fine particles makes it easier for the force chains which control the soil stability to buckle. As observed by Chang and Zhang (2011), the dilative behavior of the non-eroded specimen changed to a contractive behavior after erosion. In the case of a coarse grain skeleton, the loss of fine particles will make the critical state line move upwards in the e - $\log p'$ plane. The interlocking effect could, therefore, be enhanced when e_c/e increases. This might explain the observed increase of the initial peak strength of the eroded specimen in some cases (e.g. Mehdizadeh et al. 2017). Thus, when a part of the fine particles is detached from the soil skeleton, the void ratio e increases, and the critical void ratio e_c evolves according to the fines content f_c , creating a disequilibrium of internal and external forces and, consequently, a deformation of the granular assembly.

During an internal erosion experimental test, the soil specimen is subjected to constant boundary stresses, whereas the amount of eroded fine particles increases progressively. Therefore, the stress ratio η is kept constant while the peak strength ratio M_p and the initial stiffness G_η evolve as a

289 function of the density state of the soil. The shear strain can be written in an incremental form from
 290 Eq. (15):

$$291 \quad \delta\epsilon_d = -\frac{M_p^{(i)}}{G_\eta^{(i)}} \ln\left(1 - \frac{\eta^{(i)}}{M_p^{(i)}}\right) + \frac{M_p^{(i-1)}}{G_\eta^{(i-1)}} \ln\left(1 - \frac{\eta^{(i-1)}}{M_p^{(i-1)}}\right) \quad (23)$$

292 with the superscript (i) representing the current loading step and $(i-1)$ the previous loading step.

293 The volumetric strain increment can then be computed as:

$$294 \quad \delta\epsilon_v = -\frac{p'}{K^2} \delta K + A_d \left(M_{pt} - \frac{q}{p'} \right) \delta\epsilon_d [1 - \exp(-d\eta)] \quad (24)$$

295 The incremental modification of the void ratio induced by the body deformation is added to the void
 296 ratio change caused by erosion:

$$297 \quad (\delta e)_{\text{total}} = (\delta e)_{\text{er}} + \delta\epsilon_v (1 + e) \quad (25)$$

298 Under triaxial condition, the axial and radial strain increments ($\delta\epsilon_a$ and $\delta\epsilon_r$) are functions of the
 299 shear and volumetric strain increments:

$$300 \quad \delta\epsilon_a = \delta\epsilon_d + \frac{1}{3} \delta\epsilon_v, \quad \delta\epsilon_r = \frac{1}{3} \delta\epsilon_v - \frac{1}{2} \delta\epsilon_d \quad (26)$$

301 Thus, $\delta\epsilon_a$ and $\delta\epsilon_r$ can be used alternatively instead of $\delta\epsilon_d$ and $\delta\epsilon_v$.

302 The influence of the effective stress on the erosion of fine particles is considered in two parts. First,
 303 the volume change induced by the effective stress ($\text{div}(\mathbf{v}_s) = \partial(\epsilon_v)/\partial t$) has been used in the mass
 304 balance equations (3)-(6). Thus, the impact of the effective stress is implied in the volume change,
 305 which will further induce changes in the permeability as well as in the flow rate and the erosion rate,
 306 according to Eqs. (10)-(14). Secondly, the mass exchange term $\hat{n}$ for the mass balance equations (3)-

(6) is formulated to be dependent directly on the shear stress ratio η/M_p , according to Eqs. (13)-(14), as shown by experimental results (e.g. Chang and Zhang 2011). However, the impact of the confining pressure on the erodibility of fine particles still remains unclear since the results in the literature (Chang and Zhang 2011, Bendahmane et al. 2008, Luo et al. 2013, and Ke and Takahashi 2014b, Moffat and Fannin 2011) present contradictions. More advanced experimental tests with visualization of particles are needed to calibrate more precisely the relationship between the erosion rate and the stress state.

3. Simulations of tests

3.1. Description of laboratory tests

Chang and Zhang (2011) performed several hydraulic-gradient controlled downward erosion tests on gap-graded HK-CDG mixtures with a newly developed stress-controlled erosion apparatus. These experiments were performed in order to investigate the initiation and the development of internal erosion in soils subjected to multi-step fluid flow under complex stress states, as well as the stress-strain behavior of soils subjected to internal erosion. The experimental set-up consisted of a triaxial apparatus, a pressurized water supply system, a particle collection system, and a water collection system. A hollow base pedestal was designed for the eroded soil and the seepage water to pass through in the downward direction. The tested soil was obtained by mixing the commercial washed Leighton Buzzard sand (fraction E), and the completely decomposed granite (CDG) extracted from a construction site on Beacon Hill, Hong Kong, following the grain size distribution shown in Figure 1. Each triaxial specimen, 100 mm in diameter and 100 mm in high, was prepared by moist tamping to prevent soil segregation. The erosion tests were carried out under initial isotropic and anisotropic stresses with the major principal stress being parallel to the seepage direction. After a saturation

stage, the consolidation of the specimen was realized by increasing gradually the confining stress. For the tests under an anisotropic stress condition, the vertical stress was gradually increased up to the target value after the specimen had been isotropically consolidated to a given stress state. After the stress state being applied to the specimen, the pressurized water supply and the water collection system were connected to the triaxial system. The hydraulic gradient, i , was increased in stages to the final value (i.e., 0.15 per 10 min for $i \leq 1.0$, 0.25 per 10 min for $1.0 < i < 2.0$, and 0.50 per 10 min for $i \geq 2.0$). For 10 min, the hydraulic gradient was increased within the first 2 min and then kept constant for the following 8 min. Once the soil erosion was initiated, the hydraulic gradient was kept constant until no further soil loss was observed (i.e. $< 25.0\text{g/m}^2$ per 10 min). Then, the hydraulic gradient was increased to another level. A typical increase of the hydraulic gradient is illustrated in Figure 2. During the internal erosion testing, the applied hydraulic gradient, the vertical displacement, the outflow rate, and the eroded soil mass were continuously measured. The radial deformation was deduced from planar deformation observed on digital photographs. Conventional drained triaxial compression tests were then carried out to study the stress-strain behavior of the soil having been subjected to internal erosion. Note that the samples of gap-graded or broadly graded granular soils are normally more or less heterogeneous with non-uniform distribution of initial void ratio and fines content in spatial space. During the erosion process, fluidized fine particles may be blocked when passing the interface between the local “loose” area and the local “dense” area, which results in heterogeneous particle size distributions. However, not enough detail (i.e. the evolution of pore pressure along the height of the specimen) was given by Chang and Zhang (2011) to be able to consider the initial heterogeneity of the soil specimen; as a consequence, the specimens in the following simulations were assumed to be initially homogeneous.

A series of tests on the gap-graded HK-CDG mixtures samples (Chang 2012; Chang and Zhang 2011) were selected for simulations. BM-C-1, BM-C-2, and BM-C-3 were conventional drained triaxial tests on isotropically consolidated samples without erosion, under confining stresses of 50, 100, and

200 kPa, respectively. GS-C-1, GS-C-2, and GS-C-3 were erosion tests under isotropic stress states with confining stress of 50, 100 and 200 kPa, respectively. GS-C-4, GS-C-5 and GS-C-6 were erosion tests under anisotropic stress states with confining stress of 50 kPa and deviatoric stress of 50, 100 kPa and 150 kPa, respectively. For the eroded samples, drained triaxial tests were carried out starting at the stress state applied during the erosion tests. More details about the laboratory test soil can be found in (Chang 2012).

3.2. Simulation schemes

The numerical modeling scheme can be summarized in Figure 3 for granular media under constant stresses considering internal erosion. (i) represents the current step and $(i-1)$ the previous step. The set of partial differential equations were solved explicitly in time and by the finite difference method in space, the primary unknowns being the soil skeleton displacement ($\mathbf{u}_s(x,t)$), the pore pressure ($p_w(x,t)$), the porosity ($\phi(x,t)$), the fines content ($f_c(x,t)$) and the concentration of fluidized particles ($c(x,t)$). Other unknowns, such as the total discharge rate $\mathbf{q}_w(x,t)$, the density of the mixture $\bar{\rho}(x,t)$, and the intrinsic permeability $k(x,t)$ could be explicitly determined by Eqs. (1) and (10)-(12). For clarity, time t and space x variables are omitted in the equations.

Based on the above numerical scheme, the simulation could be conducted with the real dimensions of the tests by using the finite element method to investigate the temporal and spatial variations of the fines content and hydraulic conductivity during internal erosion. However, under the framework of continuum mechanics, the erosion process is uniform under the assumption of an initially uniform homogeneous specimen. In this study, the example of a well-controlled erosion coupled with the mechanical loading triaxial tests on reconstructed specimens can be seen as a case of a representative elementary volume with the hydraulic gradient across the specimen as input boundary condition.

Hence, a very interesting simplified erosion and mechanics coupled simulation model can be formulated, which should be useful in evaluating the eroded mass as well as the induced deformation of the soil element. In conventional drained triaxial test simulations before and after erosion, the confining stress was maintained constant. Thus, the ratio between the incremental deviatoric stress and the incremental mean effective stress was equal to 3. From Eqs. (16) and (17), the deviatoric stress and the volumetric strain could be obtained by imposing an incremental deviatoric strain as follows:

$$\delta q = 3G\delta\varepsilon_d \left(1 - \frac{q}{p'M_p}\right) \bigg/ \left(1 - \frac{q}{3p'}\right) \quad (27)$$

$$\delta p' = \frac{\delta q}{3} \quad (28)$$

$$\delta\varepsilon_v = \frac{\delta p'}{K} + A_d \left(M_{p'} - \frac{q}{p'}\right) \delta\varepsilon_d [1 - \exp(-d\eta)] \quad (29)$$

Note that the above conventional drained triaxial test simulations were performed on a representative elementary volume, thus the time t and the space x were not considered in the simulations.

3.3. Calibration of parameters

The physical properties of the soil mixtures are summarized in Table 1. The initial void ratio e_0 before the external stress being applied is 0.53. The mechanical parameters were calibrated as follows (see Figure 4): (a) the elastic parameters (K_0 , G_0 and n) were determined from an isotropic compression test with an assumed value of Poisson's ratio $\nu = 0.35$; (b) the friction angle ϕ_c was determined from the stress paths of the triaxial tests; (c) the CSL related parameters (λ , ξ) were measured from drained triaxial tests. It was difficult to determine these two parameters because

strain localizations appeared systematically at the end of the tests (Chang 2012); due to a lack of experimental data, the assumption of parallel critical state lines was made, and the values suggested by Yin et al. (2014) were adopted. (d) due to the lack of data concerning Chang's tests, the values of the other parameters ($e_{hc,cr0}$, $e_{hf,cr0}$, a , m and f_{th}) were assumed based on published data on other similar materials (Yin et al. 2014; Yin et al. 2016); e_{cr0} was measured from experiments (Figure 4(b)); (e) finally, the dilatancy parameters (d and A_d) were determined by fitting the stress-strain relations obtained in the triaxial tests BM-C-1, BM-C-2, and BM-C-3. The erosion parameters were calibrated by fitting the time evolution of the hydraulic conductivity and the cumulative loss of dry mass in tests GS-C-1 and GS-C-5. All determined parameters summarized in Table 2 and Table 3 were used to predict the hydro-mechanical behavior during the erosion tests and the following drained triaxial tests after erosion. Note that the parameters can also be identified by using optimization methods (Jin et al. 2018; Yin et al. 2017; Yin et al. 2018b).

Figure 5 shows the cumulative eroded soil mass and the variations in hydraulic conductivity during the internal erosion tests under different stress states. The experimental results show that the stress state during internal erosion affects significantly the hydraulic behavior of the soil. Specimens GS-C-1, GS-C-5, and GS-C-6 were tested under the same confining pressure (50 kPa), but with different deviatoric stresses: 0 kPa, 100 kPa and 150 kPa, respectively. Figure 5(a) shows the cumulative weights of the eroded soil in the three tests. It was found that the average erosion rate within the testing period increased with the increase of the deviatoric stress. Chang and Zhang (2011) attributed this observation to the fact that the primary structure formed by the coarse particles became more unstable with the increase of the applied stress ratio. Combined with the effect of the loss of fine particles that provided lateral "support" for the primary soil skeleton structure, the erosion rate in the highest stress ratio case (specimen GS-C-6) was much larger than that in the isotropic stress case (specimen GS-C-1). Moreover, due to the loss of fine particles, the permeability increased

419 significantly in the three tests as shown in Figure 5(b). The more the fine particles were lost, the
 420 larger the permeability became. Finally, the permeability reached a relatively constant value.

421 The proposed model was able to reproduce the general trend of the erosion evolution until a stable
 422 step was reached. However, some differences between experimental and numerical results could be
 423 found, especially for the evolution of the hydraulic conductivity. After the loss of a significant
 424 amount of fine particles, the soil specimen reached a new equilibrium state, where the increment of
 425 the eroded mass was generally limited. During this period, the soil permeability slightly decreased
 426 because part of the transported fine particles was assumed to be captured within the soil skeleton
 427 during the erosion process, which induced a clogging of the constrictions among the coarse particles,
 428 i.e. a self-filtration phenomenon. The decreased diameters of the effective pore throats resulted in a
 429 reduction of permeability. Only few data are available in the literature concerning the self-filtration
 430 phenomenon during an erosion test. Ke and Takahashi (2014a, 2014b) attributed the deviation of the
 431 hydraulic conductivity to the difference in homogeneity along the reconstituted soil specimens ,
 432 induced probably by the segregation during preparation and placement of the specimen. Another
 433 aspect which was not taken into account was the unknown influence of the saturation stage, which
 434 might also lead to the heterogeneity of the soil sample before erosion. Not enough detail on this
 435 particular aspect was given by Chang (2012) to calibrate the filtration term in the mass exchange
 436 equations.

437 Figure 6 presents the applied increasing hydraulic gradients for the three internal erosion simulations
 438 under different stress states. When the hydraulic gradient is increased to 0.6, i.e. the initiating
 439 hydraulic gradient i_{start} , the fine particles will start to be eroded, as shown in Figure 5. According to
 440 the above cited experimental tests of Chang and Zhang (2011), once the rate of the eroded weight
 441 became smaller than 0.02g/min, the hydraulic gradient was increased to another level. Sudden
 442 increases in the erosion rate, hydraulic conductivity and deformations of the specimen were observed

at a gradient of 1.5, i.e. the soil skeleton deformation hydraulic gradient i_{sd} , as shown in Figures 5 and 7. In the numerical simulations, the final equilibrium states were reached at a gradient around 2.2 at 200 min for GS-C-1 and at 280 min for GS-C-5 and GS-C-6. Once the self-filtration mechanism is added into the simulations, the critical hydraulic gradients could be expected to increase, and the appearance of the final equilibrium state to be delayed. With the increase of the hydraulic gradient, the pore channels previously clogged could be unblocked. This aspect will be discussed in future work based on better documented experimental data that will consider the spatial variation of the fine particles during internal erosion.

Figure 7 shows the axial and radial strains of the soil specimens caused by internal erosion. Here, the negative values mean that the sample diameter increased. Larger axial and radial strains were associated with higher stress ratios during the erosion process. The model was able to reproduce the initial small deformation stage, the skeleton deformation stage and the final equilibrium stage. A higher stress ratio was associated with larger axial and radial strains during the erosion process. Moreover, from a macroscopic point of view, the jumps in the evolution of the specimen deformation should be attributed to the changes in the hydraulic gradient. The results of the simulations under the applied increasing hydraulic gradients during internal erosion shown in Figures 6 and 7 demonstrate that the numerical approach is also able to reproduce the temporary equilibrium state reached under the applied stresses with a relatively low hydraulic gradient.

3.4. Mechanical responses after erosion

Figure 8 illustrates a comparison between the experimental and the numerical results of drained triaxial tests on samples before and after erosion. Both experimental and numerical results show that the loss of fine particles during internal erosion affects significantly the mechanical behavior of the soil. When the soil loses a significant number of fine particles, its stress-strain behavior changes

466 from dilative to contractive. When a part of the solid fraction is eroded, the density state (e_c/e)
 467 decreases and, as a consequence, the shear resistance decreases, creating additional deformation of
 468 the granular assembly.

469 The proposed numerical approach was able to reproduce the general trend of the soil behavior up to
 470 the peak strength which corresponded in the experiments to the development of strain localization
 471 within the specimens. In some cases, discrepancies between experimental and numerical results
 472 could be seen, possibly due to the difficulty of measuring accurately certain material properties, such
 473 as the elastic stiffness or the friction angle, as a function of the fines content. Another aspect which
 474 was not taken into account in the simulations was that heterogeneity within the specimen could be
 475 produced by the combined effects of transport and filtration of the fine particles. Not enough detail
 476 of this particular aspect was given by Chang (2012).

477 **4. Discussion**

478 Several numerical tests were performed on the HK-CDG samples to investigate systematically the
 479 soil behavior which lost fines content during the erosion process, as well as the influences of soil's
 480 initial density and initial fines content. After applying the external stresses, each specimen was
 481 subjected to a hydraulic gradient at constant external stresses, as shown in Figure 2.

482 **4.1. Influence of the soil's initial state on the initiation of erosion**

483 According to Figures 5 and 6, the proposed model is able to distinguish the initiating hydraulic
 484 gradient i_{start} and the soil skeleton deformation hydraulic gradient i_{sd} of the erosion process.
 485 Numerical tests were performed on the HK-CDG samples to further study the influence of the soil's
 486 initial state on the initiation of erosion. Figure 9 presents the cumulative weight of the eroded soil as

a function of hydraulic gradient for (a) different initial fines contents and (b) different initial void ratios. It is obvious that the increase of the initial fines content or the decrease of the initial void ratio increases the hydraulic gradient required to cause erosion, which appears reasonable in view of the experimental phenomenon.

4.2. Effect of internal erosion on the hydro-mechanical response

Numerical tests were performed on the HK-CDG samples, with $e_0 = 0.45$ and $f_{c0} = 0.35$. All the specimens were isotropically consolidated up to $p' = 100$ kPa and then sheared at different stress levels. Afterwards, each specimen was subjected to a hydraulic gradient while the external stresses were kept constant. Figure 10 presents the axial and the volumetric strains versus the eroded fraction of fine particles. For small stress ratios ($\eta = q/p' < 1$), a slight contraction occurred with the increase of the eroded fraction and the samples reached a final equilibrium state with an axial strain smaller than 5% after the entire erosion process. For intermediate η values ($\eta = 1.0; 1.25$), two stages could be identified. Slight contractions occur firstly, and the axial strain developed slowly. After 20% and 16.5% of the total mass being eroded for the samples under $\eta = 1.0$ and 1.25, the deformation increased much faster and the samples exhibited a large contraction. This result indicates that, at this stage, important grain rearrangements occurred in the microstructure so as to reach a new stable mechanical state. However, for $\eta \geq 1.5$, no new equilibrium state could be reached; more details can be found in the next section for similar numerical tests on denser samples. Obviously, given Δf_c (or the fines loss in terms of percentage of the total fines $\Delta f_c / f_{c0} \times 100\%$), values can be identified as the triggering factor for the development of large macroscopic deformations. Furthermore, the higher the stress ratio is during erosion, the smaller an eroded fraction will be needed in order to lead the sample to failure. The predicted axial strains of GS-C-1 ($\eta = 0$), GS-C-5 ($\eta = 1.2$) and GS-C-6 ($\eta = 1.5$) with large fines content loss are compared in Figure 11 (the solid lines correspond to loss

510 of fines content observed in experiments, and the dashed lines predict the erosion evolution in case
 511 the loss of fines content continues). It is shown that for the specimen GS-C-1 ($\eta = 0$), even if all the
 512 fines are eroded, the deformation remains below 1%; for specimens GS-C-5 ($\eta = 1.2$) and GS-C-6
 513 ($\eta = 1.5$), a temporary equilibrium state is reached at $\Delta f_c = 5\%$, and then remains stable up to 15%
 514 (for GS-C-6) and 18% (for GS-C-5) of eroded fines. The axial strain then develops very rapidly with
 515 a small loss of fines.

516 As presented in Figure 12(c) and Figure 12(f), the erosion process tends to increase the sample
 517 porosity without producing significant macroscopic deformation, especially for low and medium η
 518 values. As shown by the DEM simulations in (Scholtès et al. 2010; Wood et al. 2008; Wood and
 519 Maeda 2008), a certain amount of fine particles can be removed without significant consequence at
 520 the macroscopic scale due to the presence of floating grains not involved in the force chain network.
 521 Furthermore, the creation of a more open microstructure due to the loss of fines content dominates
 522 the effect of sample compression induced by local destabilizations.

523 In order to bring all the specimens to failure, triaxial compression was performed on the samples
 524 which stabilized after a certain fraction of the eroded mass. Figure 12 presents the simulations of the
 525 erosion for different stress ratios $\eta = q/p'$ and the following triaxial compression of the samples
 526 which stabilized at $\Delta f_c = 0.15$ and $\Delta f_c = 0.25$, respectively. These results demonstrate that the
 527 increase of the porosity produced a change in the specimen behavior from dilative to contractive. As
 528 shown also in Figure 10, the strain path was linked to the stress ratio. It is remarkable that the
 529 limiting threshold of η under which the sample failed during erosion was generally smaller than the
 530 value of q/p' at critical state (η_{cs}) obtained from the drained triaxial tests and dependent on the
 531 amount of the loss of fines. For a high degree of erosion (i.e. $\Delta f_c = 0.25$ as shown in Figure 12d-f),
 532 the specimen developed large compaction during erosion, even though the stress ratio $\eta = 1.0$ was far

from its value at the critical state ($\eta_{cs} = 1.68$). Even if the soil became denser and, therefore, somewhat stronger, large deformations might occur, leading to heavy damages to the earth structures. As stated in (Hicher 2013), granular assemblies can develop instability at a shear stress level much lower than the critical state failure line; the so-called diffuse failure can occur in highly eroded soils. Besides, the results demonstrate that the proposed model was able to take into account the evolution of the critical state which was different for the degraded specimens in comparison to the intact ones.

4.3. Influence of the soil's initial density on the hydro-mechanical response

Numerical tests were performed on dense samples of HK-CDG mixture, with $e_0 = 0.35$ and $f_{c0} = 0.35$, in order to evaluate the influence of the initial density of the soil on the mechanical response during internal erosion. By comparing Figure 13 with Figure 10, it can be concluded that, at a given stress ratio, a denser sample is more resistant and less inclined to deform when fine particles are progressively eroded. A larger Δf_c value is, therefore, necessary to trigger the development of large macroscopic deformations. For high stress ratios ($\eta \geq 1.5$), the specimens dilated with the loss of fines. Let us consider the specimen with $\eta = 1.6$ as an example. The volumetric and axial strains of the specimen increased slowly to 0.2% and 1.4%, respectively, until $\Delta f_c = 12.5\%$. Afterwards, the volume of the specimen increased rapidly, indicating that the mechanical state of the soil changed from stable to unstable, leading to the transition of the development of the axial strain from a slow to a large increase. At $\Delta f_c = 18.9\%$, a sudden decrease of the volume indicated the failure of the specimen, resulting in a high increase of the axial strain from $\varepsilon_a = 5.9\%$ to an unlimited value. The final failure of the specimen was linked to the collapse of the initial microstructure, leading to the rapid decrease of the specimen volume.

Figure 14 presents the simulations of erosion for different stress ratios $\eta=q/p'$ and the following triaxial compression of the samples which stabilized at $\Delta f_c = 0.15$ for (a-c) and $\Delta f_c = 0.25$ for (d-f), respectively. Compared to Figure 12, the results confirmed that, for initially denser specimens, the initial microstructure supported more loss of fine particles with limited macroscopic deformation.

4.4. Influence of the initial fines content on the hydro-mechanical response

Natural soils can contain different proportions of fine particles. The influence of the initial fines content on the mechanical behavior during erosion was evaluated by a series of numerical tests on HK-CDG mixture with $e_0 = 0.45$, $f_{c0} = 0.2$. Figure 15 presents the specimen deformations in the simulations of erosion for different stress ratios $\eta=q/p'$ on HK-CDG mixture with $f_{c0} = 0.2$. By comparing Figure 10 and Figure 15, it can be concluded that, for a low initial fines content, more loss of fine particles is necessary to trigger large deformations. Let us consider the specimen with $\eta = 1.65$ as an example. In the cases $f_{c0} = 0.35$ and 0.2 , respectively, the critical Δf_c necessary to trigger the failure are 1.5% and 15.5% respectively. This can be understood from the phenomenological constitutive relation $f_c - e_{cr0}$. The reference critical void ratio e_{cr0} corresponding to the initial fines content f_{c0} is shown in Figure 4 (b). It can be seen that the value of e_{cr0} at $f_{c0} = 0.2$ is larger than that at $f_{c0} = 0.35$, leading to a higher initial position of the critical state line in the $e - p'$ plane. Therefore, the specimen with $f_{c0} = 0.2$ is in a denser state than the specimen with $f_{c0} = 0.35$, evaluated by the value of e_0/e_c . This specimen remains stable until a large number of fine particles are eroded. Nevertheless, the specimen under a large stress ratio exhibited a dilatant behavior during the erosion process.

574 **5. Conclusion**

575 This study provides a novel contribution to the numerical approach of quantifying the impact of
 576 internal erosion on the mechanical behavior of granular soils. The detachment and transport of fine
 577 particles induced by internal erosion has been modeled by a mass exchange between the solid and the
 578 fluid phases. The governing equations were formulated based on the mass balance of four assumed
 579 constituents: the stable fabric of the solid skeleton, the erodible fines, the fluidized particles, and the
 580 fluid. A non-linear incremental model was adopted in order to obtain a non-linear stress-strain
 581 relationship for the soil mixture. The model was enhanced by the introduction of the critical state
 582 concept and by formulating the influence of the fines content on the critical state line in the $e-p'$
 583 plane based on experimental results in order to take into account the impact of the amount of eroded
 584 fines on soil deformability and strength.

585 An erosion and mechanics coupled model was formulated which is practical useful to evaluate the
 586 eroded mass as well as deformation of soil specimen during internal erosion. This practical model
 587 was used to simulate the behavior of HK-CDG mixtures before, during, and after erosion through
 588 triaxial tests. After a significant amount of fine particle loss, the stress-strain behavior of the soil
 589 changed from dilative to contractive with the shear resistance decreasing. The comparison between
 590 experimental results and simulations demonstrated that the model can reproduce with a reasonable
 591 success the initiation of internal erosion, the sudden increases in erosion rate, the change in hydraulic
 592 conductivity and the deformations of the specimen. The results confirmed that the deformation was
 593 linked to the stress ratio under which the erosion process was active. Note that it is in our interest to
 594 understand better the development of internal erosion. The experimental analysis on erosion induced
 595 deformations under controlled stress states is still in its infancy, not to mention the systematic
 596 analysis of the influence of the soil's initial states (initial relative density and fines content) under
 597 different stress states. Therefore, the influence of the stress state and the soil's initial states (relative

598 density and fines content) were investigated from a numerical standpoint. Interestingly, besides the
 599 stress ratio, the amount of loss of fines indicating the yielding from a stable to an unstable
 600 mechanical response appeared to be related to the initial density as well as to the initial fines content
 601 of the soil mixture. These results should provide some inspiration for the design of future
 602 experiments in order to better understand the physics of internal erosion and its impact on the soil
 603 behavior.

604 It is worth mentioning that this study does contain some limitations which could be remediated in
 605 future work. The consideration of the self-filtration process and the initial heterogeneity of the
 606 specimen might influence the critical hydraulic gradient and delay the final equilibrium state. More
 607 advanced laboratory testing in a triaxial permeameter with well-documented data on the spatial
 608 variations during internal erosion will be needed for the development, calibration, validation and
 609 verification of the model.

610 **Acknowledgement**

611 The financial support provided by both the National Natural Science Foundation of China
 612 (51579179) and the National Institute for Industrial Environment and Risks of France (INERIS) is
 613 gratefully acknowledged.

614 **References**

- 615 Bendahmane, F., Marot, D., and Alexis, A. 2008. Experimental parametric study of suffusion and
 616 backward erosion. *Journal of geotechnical and geoenvironmental engineering*, 134(1): 57-67.
 617 Bonelli, S., and Marot, D. On the modelling of internal soil erosion. *In* The 12th International
 618 Conference of International Association for Computer Methods and Advances in
 619 Geomechanics (IACMAG). 2008. p. 7.
 620 Borja, R.I. 2006. On the mechanical energy and effective stress in saturated and unsaturated porous
 621 continua. *International Journal of Solids and Structures*, 43(6): 1764-1786.
 622 Burenkova, V. 1993. Assessment of suffusion in non-cohesive and graded soils. *Filters in*
 623 *geotechnical and hydraulic engineering*. Balkema, Rotterdam: 357-360.

- Chang, D. 2012. Internal erosion and overtopping erosion of earth dams and landslide dams. The Hong Kong University of Science and Technology.
- Chang, D., and Zhang, L. 2011. A stress-controlled erosion apparatus for studying internal erosion in soils. *Geotechnical Testing Journal*, 34(6): 579-589.
- Cividini, A., and Gioda, G. 2004. Finite-element approach to the erosion and transport of fine particles in granular soils. *International Journal of Geomechanics*, 4(3): 191-198.
- Cividini, A., Bonomi, S., Vignati, G.C., and Gioda, G. 2009. Seepage-induced erosion in granular soil and consequent settlements. *International Journal of Geomechanics*, 9(4): 187-194.
- Crosta, G., and Prisco, C.d. 1999. On slope instability induced by seepage erosion. *Canadian Geotechnical Journal*, 36(6): 1056-1073.
- de Boer, R. 2000. Contemporary progress in porous media theory. *Applied Mechanics Reviews*, 53(12): 323-370.
- Fell, R., Wan, C.F., Cyganiewicz, J., and Foster, M. 2003. Time for development of internal erosion and piping in embankment dams. *Journal of geotechnical and geoenvironmental engineering*, 129(4): 307-314.
- Foster, M., Fell, R., and Spannagle, M. 2000. The statistics of embankment dam failures and accidents. *Canadian Geotechnical Journal*, 37(5): 1000-1024.
- Foster, M., and Fell, R. 2001. Assessing embankment dam filters that do not satisfy design criteria. *Journal of geotechnical and geoenvironmental engineering*, 127(5): 398-407.
- Hicher, P.-Y. 2013. Modelling the impact of particle removal on granular material behaviour. *Géotechnique*, 63(2): 118.
- Hosn, R.A., Sibille, L., Benahmed, N., and Chareyre, B. 2018. A discrete numerical model involving partial fluid-solid coupling to describe suffusion effects in soils. *Computers and Geotechnics*, 95: 30-39.
- Hu, W., Hicher, P.-Y., Scaringi, G., Xu, Q., Van Asch, T., and Wang, G. 2018. Seismic precursor to instability induced by internal erosion in loose granular slopes. *Géotechnique*: 1-13.
- Jin, Y.-F., Wu, Z.-X., Yin, Z.-Y., and Shen, J.S. 2017. Estimation of critical state-related formula in advanced constitutive modeling of granular material. *Acta Geotechnica*, 12(6): 1329-1351.
- Jin, Y.-F., Yin, Z.-Y., Wu, Z.-X., and Zhou, W.-H. 2018. Identifying parameters of easily crushable sand and application to offshore pile driving. *Ocean Engineering*, 154: 416-429.
- Jin, Y.F., Yin, Z.Y., Shen, S.L., and Hicher, P.Y. 2016. Selection of sand models and identification of parameters using an enhanced genetic algorithm. *International journal for numerical and analytical methods in geomechanics*, 40(8): 1219-1240.
- Jin, Y.F., and Yin, Z.Y. 2018. ErosLab: A modelling tool for soil tests. *Advances in Engineering Software*, 121: 84-97.
- Ke, L., and Takahashi, A. 2014a. Experimental investigations on suffusion characteristics and its mechanical consequences on saturated cohesionless soil. *Soils and foundations*, 54(4): 713-730.
- Ke, L., and Takahashi, A. 2014b. Triaxial erosion test for evaluation of mechanical consequences of internal erosion. *Geotechnical Testing Journal*, 37(2): 347-364.
- Ke, L., and Takahashi, A. 2015. Drained monotonic responses of suffusional cohesionless soils. *Journal of geotechnical and geoenvironmental engineering*, 141(8): 04015033.
- Ke, L., Ouyang, M., Horikoshi, K., and Takahashi, A. 2016. Soil deformation due to suffusion and its consequences on undrained behavior under various confining pressures. *Japanese Geotechnical Society Special Publication*, 2(8): 368-373.
- Kenney, T., and Lau, D. 1985. Internal stability of granular filters. *Canadian Geotechnical Journal*, 22(2): 215-225.
- Kenney, T., and Lau, D. 1986. Internal stability of granular filters: Reply. *Canadian Geotechnical Journal*, 23(3): 420-423.
- Kézdi, A. 1979. Soil physics-selected topics-developments in geotechnical engineering-25.

- Li, M., and Fannin, R.J. 2008. Comparison of two criteria for internal stability of granular soil. *Canadian Geotechnical Journal*, 45(9): 1303-1309.
- Lominé, F., Scholtès, L., Sibille, L., and Poullain, P. 2013. Modeling of fluid–solid interaction in granular media with coupled lattice Boltzmann/discrete element methods: application to piping erosion. *International journal for numerical and analytical methods in geomechanics*, 37(6): 577-596.
- Luo, Y., Qiao, L., Liu, X., Zhan, M., and Sheng, J. 2013. Hydro-mechanical experiments on suffusion under long-term large hydraulic heads. *Natural Hazards*, 65(3): 1361-1377.
- Mansouri, M., El Youssoufi, M.S., and Nicot, F. 2017. Numerical simulation of the quicksand phenomenon by a 3D coupled Discrete Element - Lattice Boltzmann hydromechanical model. *International journal for numerical and analytical methods in geomechanics*, 41(3): 338-358.
- Marot, D., Rochim, A., Nguyen, H.-H., Bendahmane, F., and Sibille, L. 2016. Assessing the susceptibility of gap-graded soils to internal erosion: proposition of a new experimental methodology. *Natural Hazards*, 83(1): 365-388.
- Mehdizadeh, A., Disfani, M.M., Evans, R., and Arulrajah, A. 2017. Progressive internal erosion in a gap-graded internally unstable soil: mechanical and geometrical effects. *International Journal of Geomechanics*, 18(3): 04017160.
- Moffat, R.A., and Fannin, R.J. 2006. A large permeameter for study of internal stability in cohesionless soils. *Geotechnical Testing Journal*, 29(4): 273-279.
- Moffat, R.A., Fannin, R.J., and Garner, S.J. 2011. Spatial and temporal progression of internal erosion in cohesionless soil. *Canadian Geotechnical Journal*, 48(3): 399-412.
- Muir Wood, D. 2007. The magic of sands—the 20th Bjerrum Lecture presented in Oslo, 25 November 2005. *Canadian Geotechnical Journal*, 44(11): 1329-1350.
- Muir Wood, D., Maeda, K., and Nukudani, E. 2010. Modelling mechanical consequences of erosion. *Géotechnique*, 60(6): 447-457.
- Papamichos, E., Vardoulakis, I., Tronvoll, J., and Skjaerstein, A. 2001. Volumetric sand production model and experiment. *International journal for numerical and analytical methods in geomechanics*, 25(8): 789-808.
- Reboul, N. 2008. Transport de particules dans les milieux granulaires: Application à l'érosion interne. Ecully, Ecole centrale de Lyon.
- Reddi, L.N., Lee, I.-M., and Bonala, M.V. 2000. Comparison of internal and surface erosion using flow pump tests on a sand-kaolinite mixture. *Geotechnical Testing Journal*, 23(1): 116-122.
- Revil, A., and Cathles, L. 1999. Permeability of shaly sands. *Water Resources Research*, 35(3): 651-662.
- Rochim, A., Marot, D., Sibille, L., and Thao Le, V. 2017. Effects of Hydraulic Loading History on Suffusion Susceptibility of Cohesionless Soils. *Journal of geotechnical and geoenvironmental engineering*, 143(7): 04017025.
- Rönnqvist, H., Fannin, J., and Viklander, P. 2014. On the use of empirical methods for assessment of filters in embankment dams. *Géotechnique Letters*, 4(4): 272-282.
- Sari, H., Chareyre, B., Catalano, E., Philippe, P., and Vincens, E. Investigation of internal erosion processes using a coupled dem-fluid method. *In Particles 2011 II International Conference on Particle-Based Methods*, E. Oate and DRJ Owen (Eds), Barcelona. 2011. pp. 1-11.
- Schaufler, A., Becker, C., and Steeb, H. 2013. Infiltration processes in cohesionless soils. *ZAMM - Journal of Applied Mathematics and Mechanics/Zeitschrift für Angewandte Mathematik und Mechanik*, 93(2 - 3): 138-146.
- Scholtès, L., Hicher, P.-Y., and Sibille, L. 2010. Multiscale approaches to describe mechanical responses induced by particle removal in granular materials. *Comptes Rendus Mécanique*, 338(10-11): 627-638.

- 723 Sherard, J. Sinkholes in dams of coarse, broadly graded soils. 13th Int. In Congress on Large Dams,
724 New Delhi Q. 1979. p. R2.
- 725 Sibille, L., Marot, D., and Sail, Y. 2015a. A description of internal erosion by suffusion and induced
726 settlements on cohesionless granular matter. *Acta Geotechnica*, 10(6): 735-748.
- 727 Sibille, L., Lominé, F., Poullain, P., Sail, Y., and Marot, D. 2015b. Internal erosion in granular
728 media: direct numerical simulations and energy interpretation. *Hydrological Processes*, 29(9):
729 2149-2163.
- 730 Skempton, A., and Brogan, J. 1994. Experiments on piping in sandy gravels. *Géotechnique*, 44(3):
731 449-460.
- 732 Slangen, P., and Fannin, R. 2016. A Flexible Wall Permeameter for Investigating Suffusion and
733 Suffosion. *Geotechnical Testing Journal*, 40(1): 1-14.
- 734 Stavropoulou, M., Papanastasiou, P., and Vardoulakis, I. 1998. Coupled wellbore erosion and
735 stability analysis. *International journal for numerical and analytical methods in*
736 *geomechanics*, 22(9): 749-769.
- 737 Steeb, H., and Diebels, S. 2003. A thermodynamic-consistent model describing growth and
738 remodeling phenomena. *Computational materials science*, 28(3): 597-607.
- 739 Sterpi, D. 2003. Effects of the erosion and transport of fine particles due to seepage flow.
740 *International Journal of Geomechanics*, 3(1): 111-122.
- 741 Uzuoka, R., and Borja, R.I. 2012. Dynamics of unsaturated poroelastic solids at finite strain.
742 *International journal for numerical and analytical methods in geomechanics*, 36(13): 1535-
743 1573.
- 744 Uzuoka, R., Ichiyama, T., Mori, T., and Kazama, M. Hydro-mechanical analysis of internal erosion
745 with mass exchange between solid and water. *In* 6th International Conference on Scour and
746 Erosion. 2012. pp. 655-662.
- 747 Vardoulakis, I., Stavropoulou, M., and Papanastasiou, P. 1996. Hydro-mechanical aspects of the
748 sand production problem. *Transport in porous media*, 22(2): 225-244.
- 749 Wan, C.F., and Fell, R. 2004. Investigation of rate of erosion of soils in embankment dams. *Journal*
750 *of geotechnical and geoenvironmental engineering*, 130(4): 373-380.
- 751 Wan, C.F., and Fell, R. 2008. Assessing the potential of internal instability and suffusion in
752 embankment dams and their foundations. *Journal of geotechnical and geoenvironmental*
753 *engineering*, 134(3): 401-407.
- 754 Wood, D., Maeda, K., and NUKUDANI, E. 2008. c. *In* Fourth International Conference on Scour
755 and Erosion. pp. 491-496.
- 756 Wood, D.M., and Maeda, K. 2008. Changing grading of soil: effect on critical states. *Acta*
757 *Geotechnica*, 3(1): 3-14.
- 758 Xu, Y., and Zhang, L. 2009. Breaching parameters for earth and rockfill dams. *Journal of*
759 *geotechnical and geoenvironmental engineering*, 135(12): 1957-1970.
- 760 Yin, Z.-Y., Zhao, J., and Hicher, P.-Y. 2014. A micromechanics-based model for sand-silt mixtures.
761 *International Journal of Solids and Structures*, 51(6): 1350-1363.
- 762 Yin, Z.-Y., Huang, H.-W., and Hicher, P.-Y. 2016. Elastoplastic modeling of sand-silt mixtures.
763 *Soils and foundations*, 56(3): 520-532.
- 764 Yin, Z.-Y., Wu, Z.-X., and Hicher, P.-Y. 2018a. Modeling Monotonic and Cyclic Behavior of
765 Granular Materials by Exponential Constitutive Function. *Journal of Engineering Mechanics*,
766 144(4): 04018014.
- 767 Yin, Z.-Y., Jin, Y.-F., Shen, S.-L., and Huang, H.-W. 2017. An efficient optimization method for
768 identifying parameters of soft structured clay by an enhanced genetic algorithm and elastic-
769 viscoplastic model. *Acta Geotechnica*, 12(4): 849-867.
- 770 Yin, Z.Y., Jin, Y.F., Shen, J.S., and Hicher, P.Y. 2018b. Optimization techniques for identifying soil
771 parameters in geotechnical engineering: Comparative study and enhancement. *International*
772 *journal for numerical and analytical methods in geomechanics*, 42(1): 70-94.

- 773 Zhang, F., Li, M., Peng, M., Chen, C., and Zhang, L. 2018. Three-dimensional DEM modeling of the
774 stress-strain behavior for the gap-graded soils subjected to internal erosion. *Acta*
775 *Geotechnica*: 1-17.
- 776 Zhang, L., and Chen, Q. 2006. Seepage failure mechanism of the Gouhou rockfill dam during
777 reservoir water infiltration. *Soils and foundations*, 46(5): 557-568.
- 778 Zhang, L., and Du, J. 1997. Effects of abutment slopes on the performance of high rockfill dams.
779 *Canadian Geotechnical Journal*, 34(4): 489-497.
- 780 Zhang, L., Xu, Y., and Jia, J. 2009. Analysis of earth dam failures: A database approach. *Georisk*,
781 3(3): 184-189.
- 782 Zhang, X., Wong, H., Leo, C., Bui, T., Wang, J., Sun, W., and Huang, Z. 2013. A thermodynamics-
783 based model on the internal erosion of earth structures. *Geotechnical and Geological*
784 *Engineering*, 31(2): 479-492.
- 785 Zhao, J., and Shan, T. 2013. Coupled CFD-DEM simulation of fluid-particle interaction in
786 geomechanics. *Powder technology*, 239: 248-258.

788 **Figure captions**

789 Figure 1. Grain size distribution of the tested HK-CDG mixture

790 Figure 2. Illustration of increasing hydraulic gradient applied during internal erosion test

791 Figure 3. Computation flowchart for internal erosion under constant stresses

792 Figure 4. (a) Isotropic compression test simulation and critical state; (b) fitted reference critical void
793 ratio versus fines content for HK CDG mixture

794 Figure 5. Comparison between experimental results and simulations for HK CDG mixture during
795 erosion tests under different stress states: (a) Cumulative eroded soil mass and (b) variations of the
796 coefficient of permeability

797 Figure 6. Increasing hydraulic gradients applied during internal erosion for simulations

798 Figure 7. Comparison of the deformation of the specimen between experimental results and
799 simulations for HK CDG mixture during erosion tests under different stress states: (a) axial strain
800 and (b) radial strain.

801 Figure 8. Comparison between experimental results and simulations for HK-CDG mixture before
802 and after erosion: (a,c) deviatoric stress versus axial strain; (b,d) void ratio versus axial strain

803 Figure 9. Cumulative weight of eroded soil as a function of hydraulic gradient for (a) different initial
804 fines contents; and (b) different initial void ratios

805 Figure 10. Specimen deformations as a function of the eroded fraction of fine particles in the
806 simulations of erosion for different stress ratios $\eta = q/p'$: (a) axial strains; (b) volumetric strains

807 Figure 11. Simulated results of the calibrated erosion tests with continuing fines loss

808 Figure 12. Simulations of erosion for different stress ratio $\eta=q/p'$ and the following triaxial
 809 compression which stabilized at $\Delta f_c = 0.15$ for (a - c), and $\Delta f_c = 0.25$ for (d - f), respectively: the
 810 thick blue lines indicate the triaxial compression of the initial specimen, the dashed thin lines
 811 indicate the erosion process, the solid lines indicate the following triaxial compression of the eroded
 812 samples

813 Figure 13. Specimen deformations in the simulations of erosion for different stress ratio $\eta=q/p'$ on
 814 dense HK-CDG mixture with $e_0 = 0.35$: (a) axial strains and (b) volumetric strains as a function of
 815 eroded fraction of fine particles.

816 Figure 14. Simulations of erosion on initially dense HK-CDG mixture with $e_0 = 0.35$ for different
 817 stress ratio $\eta=q/p'$ and the following triaxial compression which stabilized at $\Delta f_c = 0.15$ for (a-c),
 818 and $\Delta f_c = 0.25$ for (d-f) respectively: thick blue lines indicate the triaxial compression of the initial
 819 specimen, dashed thin lines indicate the erosion process, solid lines indicate the triaxial compression
 820 of the eroded samples

821 Figure 15. Specimen deformations in the simulations of erosion for different stress ratios $\eta=q/p'$ on
 822 sand mixture with $f_{c0} = 0.2$: (a,b) axial and volumetric strains as a function of the eroded fraction of
 823 fine particles; (c,d) porosity and volumetric strain as a function of axial strain.

1 **Appendix A1. Four-constituent continuum model**

2 In a given Representative Elementary Volume (REV), dV consisting of the four constituents, the
3 volume fraction of a single constituent x is expressed as:

$$4 \quad n^i(x, t) = \frac{dV^i(x, t)}{dV} \quad (\text{A.1})$$

5 with $i = \{ss, se, ff, fp\}$ denoting the 4 constituents: the stable fabric of the solid skeleton, the erodible
6 fines, the fluidized particles and the pure fluid phase; dV^x denoting the volume of the corresponding
7 constituent.

8 At a material point level, the mass balance for the i phase is given, neglecting the hydro-mechanical
9 dispersion tensor, by Schaufler et al. (2013):

$$10 \quad \frac{\partial(\rho^i)}{\partial t} + \text{div}(\rho^i \mathbf{v}^i) = \rho^{ex,i} \quad (\text{A.2})$$

11 where $\rho^{ex,i}$ and $\mathbf{v}^i$ denote, respectively, the mass exchange term and the velocity of the
12 corresponding constituent. The mass balances for the four constituents can be reduced to the
13 corresponding volume balance:

$$14 \quad \frac{\partial(n^i)}{\partial t} + \text{div}(n^i \mathbf{v}^i) = n^{ex,i} \quad (\text{A.3})$$

15 $n^{ex,x}$ is the term of the volume of mass exchange.

16 The porosity field $\phi(x, t)$, the amount of erodible fines $f_c(x, t)$ and the concentration of the
17 fluidized particles $c(x, t)$ are defined as follows:

18

$$\phi = n^{ff} + n^{fp}, f_c = \frac{n^{se}}{1 - \phi}, c = \frac{n^{fp}}{\phi}$$

(A.4)

19

The phase transition of the fine particles from solid to fluidized particles leads to:

20

$$-n^{ex,fp} = n^{ex,se} = \hat{n}, n^{ex,ss} = 0, n^{ex,ff} = 0$$

(A.5)

21

The mass balance equations are then given by Eqs. (3)-(6).

1 **Tables**

2 Table 1 Physical properties of the tested soil mixtures

Density of fluid	ρ_f	1.00 g/cm ³
Density of solids	ρ_s	2.65 g/cm ³
Kinematic viscosity of fluid	η_k	5.0×10 ⁻⁶ m ² ·s ⁻¹
Initial porosity	ϕ_0	0.34
Initial permeability	k	7.5×10 ⁻⁵ m·s ⁻¹
Initial fines content	f_{c0}	0.35

3

4 Table 2. Mechanical constants of HK-CDG mixture

Elastic parameters			Dilatancy parameters		CSL-related parameters				
K_0/MPa	G_0/MPa	n	d	A_d	$e_{hc,cr0}$	$e_{fc,cr0}$	ξ	λ	ϕ_c
50	16.7	0.95	18	0.35	0.8	0.86	0.45	0.03	40.5

5

6 Table 3. Erosion constants of HK-CDG mixture

Fines parameters			Erosion parameters				
a	m	f_{th}	λ_e	α_1	α_2	α_3	m_k
0.79	0.46	0.28	1	0.8	2.7	0.05	4

7

Figure 1. Grain size distribution of the tested HK-CDG mixture

Figure 2. Illustration of increasing hydraulic gradient applied during internal erosion test

Figure 3. Computation flowchart for internal erosion under constant stresses

Figure 4. (a) Isotropic compression test simulation and critical state; (b) fitted reference critical void ratio versus fines content for HK CDG mixture

Figure 5. Comparison between experimental results and simulations for HK CDG mixture during erosion tests under different stress states: (a) Cumulative eroded soil mass and (b) variations of the coefficient of permeability

Figure 6. Increasing hydraulic gradients applied during internal erosion for simulations

Figure 7. Comparison of the deformation of the specimen between experimental results and simulations for HK CDG mixture during erosion tests under different stress states: (a) axial strain and (b) radial strain.

Figure 8. Comparison between experimental results and simulations for HK-CDG mixture before and after erosion: (a,c) deviatoric stress versus axial strain; (b,d) void ratio versus axial strain

Figure 9. Cumulative weight of eroded soil as a function of hydraulic gradient for (a) different initial fines contents; and (b) different initial void ratios

Figure 10. Specimen deformations as a function of the eroded fraction of fine particles in the simulations of erosion for different stress ratios : (a) axial strains; (b) volumetric strains

Figure 11. Simulated results of the calibrated erosion tests with continuing fines loss

Figure 12. Simulations of erosion for different stress ratio and the following triaxial compression which stabilized at for (a - c), and for (d - f), respectively: the thick blue lines indicate the triaxial compression of the initial specimen, the dashed thin lines indicate the erosion process, the solid lines indicate the following triaxial compression of the eroded samples

Figure 13. Specimen deformations in the simulations of erosion for different stress ratio on dense HK-CDG mixture with : (a) axial strains and (b) volumetric strains as a function of eroded fraction of fine particles.

Figure 14. Simulations of erosion on initially dense HK-CDG mixture with $\sigma_1/\sigma_3 = 1.5$ for different stress ratio σ_1/σ_3 and the following triaxial compression which stabilized at $\sigma_1/\sigma_3 = 1.5$ for (a-c), and $\sigma_1/\sigma_3 = 2.0$ for (d-f) respectively: thick blue lines indicate the triaxial compression of the initial specimen, dashed thin lines indicate the erosion process, solid lines indicate the triaxial compression of the eroded samples

Figure 15. Specimen deformations in the simulations of erosion for different stress ratios on sand mixture with : (a,b) axial and volumetric strains as a function of the eroded fraction of fine particles; (c,d) porosity and volumetric strain as a function of axial strain.